



RACO[®]
A Division of Hubbell Incorporated (Delaware)

REDI-LOC[®] III

The Perfect Solution for Prefab Applications!

Applications


- RACO REDI-LOC III is used to terminate and secure MC, MCI, MCI-A and Armored Cable into a ½" knockout.

Features

- No tools needed to assemble to end of cable or to install into box or enclosure
- Pre assembled anti-short bushing will not fall out during installation
- Easy installation - simply push the cable into the fitting, then push connector into the box or enclosure
- Can be removed without tools and is reusable
- Rugged, one piece design
- Fits all standard ½" knockouts
- Made from Die Cast Zinc, Steel, and Polycarbonate (Bushing)



Push on cable



Push into box



Squeeze - pull out of box

Specifications for Part No. 2750 and 2750BULK

PATENT PENDING

RACO [®] REDI-LOC [®] III					
Catalog Number	Cable Size	Ship Ctn. Qty.	Unit Ctn. Qty.	Weight per 100	Carton I 2 of 5
2750	AC Steel & Al 14/2-10/3 (0.400"-0.618" Dia.) MC/MCI/MCI-A Steel, Al, & HCF 14/2-10/3 (0.395"-0.638" Dia.)	200	50	6 Lbs.	50050169027504
2750BULK	3/8" RWF MC Steel & Al	500	—	6 Lbs.	50050169927507



RACO[®]
A Division of Hubbell Incorporated (Delaware)

3902 West Sample St. P.O. Box 4002
South Bend, IN 46619-4002
TEL: 574-234-7151 FAX: 574-234-0625
www.hubbell-raco.com

Distributed By:

